

FH – PVC – supported

High rise - travelling height maximum 400m



Drawing according to article number 161448 - Type 8292-F



Descrizione

Elevator suspension cable for indoor and panoramic elevators

Applicazione

To comply with the correct installation procedures please refer to the Datwyler installation manual which is available separately

Costruzione

Core flexible	class 5
Core insulation	PVC
Supporting members	ST = Steel, diameter in [mm]

Proprietà generali

Coax	grigio
Core	black, white numbered, G = with green-yellow core(s)
Pair/quad	various colours or black with white numbers
Operating temperature	-15 °C - +70 °C
Colore della guaina esterna	grigio
Materiale della guaina esterna	PVC

Proprietà elettriche

Rated voltage Uo/U	according to table
--------------------	--------------------

Proprietà meccaniche

Acceleration	1,2 m/s ²
Maximum free suspension	220 m
Maximum running speed	12 m/s
Maximum travelling height	400 m
Recommended loop diameter	according to table, tolerance -50/+100 mm

Standards

Standard per cavi flessibili di controllo dell'ascensore	EN 50214
--	----------

Versioni

Codice art.	Prodotto	Design del cavo	Tasso di CU [kg/km]	Weight [kg/km]	GTIN / EAN
157219	7877-F	40 x 0.75 mm ²	309	1.099	40393910080025
185284	7877-F	60 x 0.75 mm ²	446	1.597	40393910077124
161448	8292-F	40 G 0.75 + 2 x 4 x 0.50 mm ² (STQ) + 1 CX 75 Ω	400	1.372	40393910079937

Con riserva di modifiche tecniche

A partire da 2021-08-05 08:33:41