


KU-T 1/8 tool-less Cat.5e

RJ45 module, unshielded, Category 5e



KU-T 1/8 tool-less RJ45 module, unshielded, Cat.5e, in white or black

Descrizione

For the transmission of digital and analogue voice, video and data signals.
 Suitable for all Class D applications respectively Class E Channels in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-B.2-10.
 Housing made of high-impact resistant, flame retardant compound, UL94V-0 rated, with Keystone mounting clip.
 Contact spring with phosphor bronze alloy, plated with gold.
 IDC made of phosphor bronze alloy. Information:
 Suitable for the same faceplates and surface mount boxes as Datwyler's shielded Keystone modules (KS-T).

Proprietà generali

Installation temperature	-10 °C - +60 °C
Storage temperature	-40 °C - +70 °C
Operating temperature	-20 °C - +60 °C

Proprietà elettriche

Gbit/s	A 1 Gbit/s
Schermatura	non schermati

Proprietà meccaniche

Connection type	Connettori a perforazione di isolante IDC
Solid copper wire	0.40 (AWG 26) - 0.65 (AWG 22)
Stranded copper wire	AWG26
Diameter over Insulation	0.70 mm - 1.40 mm
Re-connection	for AWG 22, AWG 23 and AWG 24 quando si usa lo stesso filo o un diametro maggiore
Re-usable	una volta

Standards

Cabling standards	ISO/IEC 11801, EN 50173-1, TIA/EIA 568-x
Cat./Class	Cat.5e / Class D
Connector standards	IEC 60603-7-2
PoE	IEEE 802.3bt Type 4 (100W)

Versioni

Codice art.	Prodotto	Colore	Peso [kg]	Unità di imballaggio	GTIN / EAN
41807200ZF	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	bianco	0,01 kg	12 pcs.	40393910087901
41807300ZF	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	nero	0,01 kg	12 pcs.	40393910087895
418072	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	bianco	0,01 kg	10 pcs.	40393910164978
418073	RJ45 module KU-T 1/8 tool-less, Cat. 5e, unshielded	nero	0,01 kg	10 pcs.	40393910164961

Con riserva di modifiche tecniche

A partire da 2023-11-27 14:35:51