

FO duplex patch cord LCD - LCD

G50/125 OM4




image similar

Description

Datwyler offers a broad range of terminated connectors for individual customer needs. For all patch cords figure 0 cables with 4.8x3.2 mm are used.

Proprietà generali

Costruzione di cavi	I-V(ZN)HH (4.8x3.2 mm)
Operating temperature	-10 °C - +60 °C

Proprietà ottiche

Connector type side A	LCD
Connector type side B	LCD
Durata della vita	1000 connections with stable attenuation values
Grado, connettore A (migliore di)	Bm2m
Grado, connettore B (migliore di)	Bm2m
IL maximal, connettore A	0,3 dB
IL maximal, connettore B	0,3 dB
IL tipico, connettore A	0,15 dB
IL tipico, connettore B	0,15 dB
Materiale ghiera	Zirconia
Reproducibility of the IL	maximal +/- 0.1dB
RL minimal, connector A	30 dB
RL minimal, connector B	30 dB
RL typical, connector A	35 dB
RL typical, connector B	35 dB
Standard connector A	IEC 61754-20
Standard connector B	IEC 61754-20
Tipologia di fibra	G50/125 OM4

Proprietà meccaniche

Bending (IEC 60794-1-21 E11, reversible fibre attenuation)	≤ 0,5 dB
Impatto	IEC 60794-1-21 E4
Minimum bending radius	50 mm
Repeated bending	IEC 60794-1-21 E6
Resistenza allo schiacciamento (IEC 60794-1-21 E3, attenuazione fibra reversibile)	≤ 0,2 dB
Ritenzione del cavo di collegamento	100 N
Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation)	200 N
Torsion (IEC 60794-1-21 E7, reversible fibre attenuation)	≤ 0,1 dB

Versions

Numero Materiale	Product	Outer sheath colour	Length (m)	Peso [kg]
433340	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	0,5	15 kg
433341	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	1	0,03 kg
433339	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	1,5	0,03 kg
433342	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	2	0,05 kg
433343	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	3	0,07 kg
433344	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	4	0,09 kg
433345	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	5	0,11 kg
433346	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	6	0,13 kg
433347	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	7	0,15 kg
433348	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	8	0,17 kg
433349	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	9	0,19 kg
433350	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	10	0,21 kg
433352	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	11	0,2 kg
433367	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	12	0,25 kg
433354	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	13	0,27 kg
433355	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	14	0,29 kg
433357	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	16	0,33 kg
433358	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	17	0,35 kg
433359	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	18	0,37 kg
433360	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	19	0,39 kg
433361	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	20	0,41 kg
433362	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	21	0,43 kg
433363	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	22	0,45 kg
433364	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	23	0,47 kg
433365	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	24	0,49 kg
433366	FO duplex patch cord LCD - LCD, G50/125 OM4	violetto	25	0,51 kg