

FO duplex patch cord LCD - LCD

E9/125 G.652.D OS2




image similar

Description

Datwyler offers a broad range of terminated connectors for individual customer needs. For all patch cords figure 0 cables with 4.8x3.2 mm are used.

Proprietà generali

Costruzione di cavi	I-V(ZN)HH (4.8x3.2 mm)
Operating temperature	-10 °C - +60 °C

Proprietà ottiche

Connector type side A	LCD
Connector type side B	LCD
Durata della vita	1000 connections with stable attenuation values
Grado, connettore A (migliore di)	B2
Grado, connettore B (migliore di)	B2
IL maximal, connettore A	0,25 dB
IL maximal, connettore B	0,25 dB
IL tipico, connettore A	0,12 dB
IL tipico, connettore B	0,12 dB
Materiale ghiera	Zirconia
Reproducibility of the IL	maximal +/- 0.1dB
RL minimal, connector A	50 dB
RL minimal, connector B	50 dB
RL typical, connector A	55 dB
RL typical, connector B	55 dB
Standard connector A	IEC 61754-20
Standard connector B	IEC 61754-20

Proprietà meccaniche

Bending (IEC 60794-1-21 E11, reversible fibre attenuation)	≤ 0,5 dB
Impatto	IEC 60794-1-21 E4
Minimum bending radius	50 mm
Repeated bending	IEC 60794-1-21 E6
Resistenza allo schiacciamento (IEC 60794-1-21 E3, attenuazione fibra reversibile)	≤ 0,2 dB
Ritenzione del cavo di collegamento	100 N
Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation)	200 N
Torsion (IEC 60794-1-21 E7, reversible fibre attenuation)	≤ 0,1 dB

Versions

Numero Materiale	Product	Outer sheath colour	Length (m)	Peso [kg]
423311	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	1	0,03 kg
423312	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	2	0,05 kg
423313	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	3	0,07 kg
423314	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	4	0,09 kg
423315	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	5	0,11 kg
423316	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	6	0,13 kg
423317	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	7	0,15 kg
423318	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	8	0,17 kg
423319	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	9	0,19 kg
423320	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	10	0,21 kg
423384	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	11	0,3 kg
423386	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	13	0,32 kg
423387	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	14	0,33 kg
423391	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	16	0,35 kg
423392	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	17	0,36 kg
423393	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	18	0,37 kg
423394	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	19	0,38 kg
423395	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	20	0,39 kg
423396	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	21	0,4 kg
423397	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	22	0,41 kg
423398	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	23	0,42 kg
423399	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	24	0,43 kg



DATWYLER

Numero Materiale	Product	Outer sheath colour	Length (m)	Peso [kg]
423370	FO duplex patch cord LCD - LCD, E9/125 G.652.D OS2	giallo	25	0,44 kg

Con riserva di modifiche tecniche

A partire da 2021-06-29 17:00:46