

FO-DCS modular subracks, 19"/4U

to take 12 FO-DCS plug-in modules / front plates 3U/7HP



Modularly equippable FO-DCS 19"/4U subrack

Description

Sturdy aluminium housing with side panels and front 19"/3U mounting brackets.

Pre-assembled with horizontal 84HP mounting rails to take a maximum of twelve 3U/7HP FO-DCS plug-in modules or front plates. The extractable excess cable length tray (1U) is equipped with a base and offers 2 big cut outs on one side and pre-cut holes on the other side.

It can be inserted to the subrack on the fourth rack unit from the rear in two ways, so that optionally the cut outs or holes can be used as cable entry openings.

The slightly recessed arrangement of the excess cable length tray allows a 19"/1U management panel with support brackets or a patch mangement tray with guide elements to be fitted at the front.

Application

The modularly equippable 19"/4U subrack can be used for a wide variety of applications, depending on the type of plug-in module or front plate.

It can be used as a modular high-density solution for up to 144 duplex ports (288 fibres) or up to 144 MTP* ports (1728 fibres) in the data centre environment.

Easy migration to all parallel optic applications, e.g. to 40/100 GbE, is possible with FO-DCS 3U/7HP MTP front plates.

General Properties					
Acceptance capacity	12 FO-DCS inserts				
Cable entry	from rear, via the cassette for excess cable length				
Capacity	84HP, up to 12 FO-DCS slide-in modules or front plates 3U/7HP				
Housing	Solid aluminium profile with side walls, integrated 19"/3U fixation on the front				



Scope of delivery

 $19^{\prime\prime}/4U$ subrack with $19^{\prime\prime}$ mounting brackets on 3U (without plug-in modules / front plates) 84HP mounting rails for 12 3U/7HP FO-DCS inserts

1U excess cable length tray, integrated, insertable from rear

Versions							
Material number	Product	Outer dimensions (HxWxD)	Colour	Material	Weight [kg]	Packing unit	
470542	FO-DCS modular subrack, 19"/4U, 84HP	178 mm x 483 mm x 295 mm	silver	Aluminium anodised	1.8 kg	1 pc.	
470642	FO-DCS modular subrack, 19"/4U, 84HP	178 mm x 483 mm x 295 mm	black	Aluminium	1.8 kg	1 pc.	
470555	FO-DCS blank partial front plate 3U/7HP		silver	Aluminium anodised	0.1 kg	1 pc.	
57159500ZY	FO-DCS blank partial front plate 3U/7HP		black	Polycarbonate (PC)	0.05 kg	1 pc.	

MTP° is a registered brand of US Conec.

Subject to technical modification As of 2022-02-02 10:33:21