

FM – Low Fire Hazard – supported

Mid rise - travelling height maximum 150m



Drawing according to article number 185124 - Type 8696-F



Beschrijving

Elevator suspension cable for indoor and panoramic elevators.

Toepassing

To comply with the correct installation procedures please refer to the Datwyler installation manual which is available separately

Constructie

Ader isolatie	low fire hazard
Buitenmantel	low fire hazard
Core flexibel	class 5
Mantelkleur	zwart
Ondersteunende leden	HTF = High tensile fibre

Algemene eigenschappen

Bedrijfstemperatuur	-15 °C - +70 °C
Coax	zwart
Kern	black, white numbered, G = with green-yellow core(s)
Pair/quad	various colours or black with white numbers

Elektrische eigenschappen

Nominale spanning Uo/U	according to table
------------------------	--------------------

Mechanische eigenschappen

Aanbevolen lusdiameter	according to table, tolerance -50/+100 mm
Maximale loopsnelheid	6,3 m/s
Maximale reishoogte	150 m
Maximale vrije schorsing	80 m
Versnelling	1,2 m/s ²

Normen / Standards

Standaard voor flexibele besturingskabels voor liften	EN 50214
---	----------

Versions

Materiaal nummer	Artikel	Mantelkleur	Cu tarief [kg\km]	Gewicht [kg\km]
185127	8622-F	zwart	139	484
185124	8696-F	zwart	142	499
191094	8872-F	zwart	232	818

Onder voorbehoud van technische wijziging

Vanaf 2020-12-15 10:05:43