


KS-TA 1/8 Cat.6/E_A, 45 degree angled

RJ45 module, shielded, Category 6/E_A

for Patch panel KS 24x-s



KS-TA 1/8 Cat.6/EA RJ45 module,
shielded, 45 degree angled



Patch panel KS 24x-s, 19"/1U, shielded



Description

For the transmission of digital and analogue voice-, video- and data signals.

The KS-TA RJ45 module exceeds the IEC 60603-7-5 standard's requirements for Cat. 6 connecting hardware up to 250 MHz.

It also fulfils all Class EA Permanent-Link (PL) requirements up to 500 MHz when combined with Category 7 or 7A data cables. Therefore it is applicable for 10-Gigabit Ethernet transmissions in accordance with IEEE 802.3.

Useable for Power over Ethernet Plus (PoE+) corresponding to IEEE 802.3at.

The module KS-TA is suitable for the patch panel KS24x-s (Article No. 418023) only.

Due to the module's 45 degree angled front patch connections can be made diagonally from left and right. Solid zinc die casting housing with mounting clip for installation in Keystone panel KS 24x-s.

Contact spring with phosphor bronze alloy, plated with gold.

For connecting the wires a wire manager is used in combination with two integrated moveable housing wings for tool-less IDC connections.

Only for cutting the wires a plane wire cutter is necessary.

Strain relief via cable tie.

The module is re-usable.

General Properties

Installation temperature	-10 °C - +60 °C
Operating temperature	-20 °C - +60 °C
Storage temperature	-40 °C - +70 °C

Electrical properties

EMC	shielded
-----	----------

Mechanical properties

Connection type	IDC insulation displacement connectors
Solid copper wire	0.50 (AWG 24) - 0.65 (AWG 22)
Stranded copper wire	AWG26/7 - AWG26/8
Diameter over Insulation	0.70 mm - 1.40 mm
Re-connection	for AWG 22, AWG 23 and AWG 24 when using the same or bigger wire diameter
Re-usable	once

Standards

Cat./Class	Cat.6 / Class E _A (Channel) when used together with Cat.7 / 7 _A data cables
Connector standards	IEC 60603-7-5
Cabling standards	ISO/IEC 11801, EN 50173-1, TIA/EIA 568-x

Versions

Material number	Product	Colour	Weight [kg]	Packing unit
418068	RJ45 module KS-TA 1/8 Cat.6/E _A shielded, 45 degree angled	silver	0.04 kg	10 pcs.