

FO patch panel OV-S

19"/1U, Splice box OV-S, G50/125 OM3

with adapters and pigtails



Fibre optic splice box OV-S, 19"/1U, extractable, configuration example with 24 SCD adapters and 48 pigtails

Description

For the termination of fibre optic cables - maximum of 96 fibres.
Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

Proprietà generali

| | |
|------------------------|--|
| Alloggiamento | metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm) |
| Capacità | up to 96 fibres |
| Dimensioni | 19"/1U |
| Impronta | numbers (silk screen printing) on frontplate |
| Ingresso cavi | rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary |
| Piastra frontale | similar to RAL 7035, similar to RAL 9005 or stainless steel |
| Scarico della trazione | with screwed cable gland |

Proprietà ottiche

| | |
|--------------------|-------------|
| Tipologia di fibra | G50/125 OM3 |
|--------------------|-------------|

Proprietà meccaniche

| | |
|------------|--|
| Adattatore | SCD, LCD, LCQ, LSH Coloured Polymer housings or ST metal housings, ceramic sleeves |
|------------|--|

Scope of delivery

- Splice box with
- two straight cable entries
 - one screwed cable gland M20
 - coloured pigtails with measurement report
 - FO adapters, fastened by screws
 - splice trays with cover
 - splice holder for 12 x crimp splice protectors
 - Delivery without splicing protection

Versions

| Numero Materiale | Product | Colour (Front-plate) | Number of adapters | Adapter | Colour (Adapter) | Orientamento adattatore | Dimensioni esterne | Pigtails | Classe della fibra | Peso [kg] | Packing unit |
|------------------|-------------------------------|----------------------|--------------------|---------|------------------|-------------------------|-----------------------|----------|--------------------|-----------|--------------|
| 41546800ZY | Splice box OV-S 2xLCD, OM3 | grigio chiaro | 2 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 4 x LC | OM3 | 2,5 kg | 1 pc. |



| Numero Materiale | Product | Colour (Front-plate) | Number of adapters | Adapter | Colour (Adapter) | Orientamento adattatore | Dimensioni esterne | Pigtails | Classe della fibra | Peso [kg] | Packing unit |
|------------------|-----------------------------|----------------------|--------------------|---------|------------------|-------------------------|-----------------------|----------|--------------------|-----------|--------------|
| 41546900ZY | Splice box OV-S 4xLCD, OM3 | grigio chiaro | 4 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 8 x LC | OM3 | 2,5 kg | 1 pc. |
| 41533600ZY | Splice box OV-S 6xLCD, OM3 | nera | 6 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 12 x LC | OM3 | 2,5 kg | 1 pc. |
| 41521200ZY | Splice box OV-S 6xLCD, OM3 | grigio chiaro | 6 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 12 x LC | OM3 | 3 kg | 1 pc. |
| 41535900ZY | Splice box OV-S 12xLCD, OM3 | nera | 12 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 24 x LC | OM3 | 3,1 kg | 1 pc. |
| 41544700ZY | Splice box OV-S 12xLCD, OM3 | nera | 12 | LCD | turchese | angled | 1 U, x 19 in x 245 mm | 24 x LC | OM3 | 2,8 kg | 1 pc. |
| 41521600ZY | Splice box OV-S 12xLCD, OM3 | grigio chiaro | 12 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 24 x LC | OM3 | 3 kg | 1 pc. |
| 41536100ZY | Splice box OV-S 24xLCD, OM3 | nera | 24 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 48 x LC | OM3 | 2,8 kg | 1 pc. |
| 41522000ZY | Splice box OV-S 24xLCD, OM3 | grigio chiaro | 24 | LCD | turchese | offset horizontal | 1 U, x 19 in x 245 mm | 48 x LC | OM3 | 3 kg | 1 pc. |
| 41545300ZY | Splice box OV-S 12xLCQ, OM3 | nera | 12 | LCQ | turchese | angled | 1 U, x 19 in x 245 mm | 48 x LC | OM3 | 2,5 kg | 1 pc. |
| 41538100ZY | Splice box OV-S 24xLCQ, OM3 | nera | 24 | LCQ | turchese | vertical | 1 U, x 19 in x 245 mm | 96 x LC | OM3 | 2,5 kg | 1 pc. |
| 41529800ZY | Splice box OV-S 24xLCQ, OM3 | grigio chiaro | 24 | LCQ | turchese | vertical | 1 U, x 19 in x 245 mm | 96 x LC | OM3 | 2,5 kg | 1 pc. |
| 41546600ZY | Splice box OV-S 2xSCD, OM3 | grigio chiaro | 2 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 4 x SC | OM3 | 2,5 kg | 1 pc. |
| 41546700ZY | Splice box OV-S 4xSCD, OM3 | grigio chiaro | 4 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 8 x LC | OM3 | 2,5 kg | 1 pc. |
| 41533300ZY | Splice box OV-S 6xSCD, OM3 | nera | 6 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 12 x SC | OM3 | 2,5 kg | 1 pc. |
| 41522400ZY | Splice box OV-S 6xSCD, OM3 | grigio chiaro | 6 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 12 x SC | OM3 | 3 kg | 1 pc. |
| 41533400ZY | Splice box OV-S 12xSCD, OM3 | nera | 12 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 24 x SC | OM3 | 2,5 kg | 1 pc. |
| 41522800ZY | Splice box OV-S 12xSCD, OM3 | grigio chiaro | 12 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 24 x SC | OM3 | 3 kg | 1 pc. |
| 41537000ZY | Splice box OV-S 24xSCD, OM3 | nera | 24 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 48 x SC | OM3 | 3,4 kg | 1 pc. |
| 41523200ZY | Splice box OV-S 24xSCD, OM3 | grigio chiaro | 24 | SCD | turchese | vertical | 1 U, x 19 in x 245 mm | 48 x SC | OM3 | 3 kg | 1 pc. |
| 41537400ZY | Splice box OV-S 6xLSH, OM3 | nera | 6 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 6 x LSH | OM3 | 2,5 kg | 1 pc. |
| 41531400ZY | Splice box OV-S 6xLSH, OM3 | grigio chiaro | 6 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 6 x LSH | OM3 | 2,5 kg | 1 pc. |
| 41537700ZY | Splice box OV-S 12xLSH, OM3 | nera | 12 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 12 x LSH | OM3 | 2,6 kg | 1 pc. |
| 41531600ZY | Splice box OV-S 12xLSH, OM3 | grigio chiaro | 12 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 12 x LSH | OM3 | 2,6 kg | 1 pc. |
| 41538000ZY | Splice box OV-S 24xLSH, OM3 | nera | 24 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 24 x LSH | OM3 | 2,8 kg | 1 pc. |
| 41531800ZY | Splice box OV-S 24xLSH, OM3 | grigio chiaro | 24 | LSH | turchese | vertical | 1 U, x 19 in x 245 mm | 24 x LSH | OM3 | 2,8 kg | 1 pc. |
| 41534600ZY | Splice box OV-S 6xST, OM3 | nera | 6 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 6 x ST | OM3 | 2,2 kg | 1 pc. |
| 41523600ZY | Splice box OV-S 6xST, OM3 | grigio chiaro | 6 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 6 x ST | OM3 | 2,5 kg | 1 pc. |
| 41535200ZY | Splice box OV-S 12xST, OM3 | nera | 12 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 12 x ST | OM3 | 2,5 kg | 1 pc. |
| 41524000ZY | Splice box OV-S 12xST, OM3 | grigio chiaro | 12 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 12 x ST | OM3 | 2,5 kg | 1 pc. |
| 41535500ZY | Splice box OV-S 24xST, OM3 | nera | 24 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 24 x ST | OM3 | 2,8 kg | 1 pc. |
| 41524400ZY | Splice box OV-S 24xST, OM3 | grigio chiaro | 24 | ST | metal | vertical | 1 U, x 19 in x 245 mm | 24 x ST | OM3 | 2,8 kg | 1 pc. |

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-02-23 15:00:16