

FO patch panel OV-S

19"/1U, Splice box OV-S, E9/125 G.652.D OS2

with adapters and pigtails



Fibre optic splice box OV-S, 19"/1U, extractable, configuration example with 24 LCD/APC adapters and 48 pigtails

Description

For the termination of fibre optic cables - maximum of 96 fibres.
Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

Proprietà generali

Alloggiamento	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Capacità	up to 96 fibres
Dimensioni	19"/1U
Impronta	numbers (silk screen printing) on frontplate
Ingresso cavi	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Piastra frontale	similar to RAL 7035, similar to RAL 9005 or stainless steel
Scarico della trazione	with screwed cable gland

Proprietà ottiche

Tipologia di fibra	E9/125 G.652.D OS2
--------------------	--------------------

Proprietà meccaniche

Adattatore	SCD, LCD, LCQ, LSH Coloured Polymer housings or ST metal housings, ceramic sleeves
------------	--

Scope of delivery

- Splice box with
- two straight cable entries
 - one screwed cable gland M20
 - coloured pigtails with measurement report
 - FO adapters, fastened by screws
 - splice trays with cover
 - splice holder for 12 x crimp splice protectors
 - Delivery without splicing protection

Versions

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
41547200ZY	Splice box OV-S 2xLCD, OS2	grigio chiaro	2	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	4 x LC	OS2	2,5 kg	1 pc.



Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
41547300ZY	Splice box OV-S 4xLCD, OS2	grigio chiaro	4	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	8 x LC	OS2	2,5 kg	1 pc.
41535700ZY	Splice box OV-S 6xLCD, OS2	nera	6	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	12 x LC	OS2	2,5 kg	1 pc.
41521000ZY	Splice box OV-S 6xLCD, OS2	grigio chiaro	6	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	12 x LC	OS2	3 kg	1 pc.
41544800ZY	Splice box OV-S 12xLCD, OS2	nera	12	LCD	blu	angled	1 U, x 19 in x 245 mm	24 x LC	OS2	2,8 kg	1 pc.
41534100ZY	Splice box OV-S 12xLCD, OS2	nera	12	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	24 x LC	OS2	2,5 kg	1 pc.
41521400ZY	Splice box OV-S 12xLCD, OS2	grigio chiaro	12	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	24 x LC	OS2	3 kg	1 pc.
41533700ZY	Splice box OV-S 24xLCD, OS2	nera	24	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	48 x LC	OS2	2,5 kg	1 pc.
41521800ZY	Splice box OV-S 24xLCD, OS2	grigio chiaro	24	LCD	blu	offset horizontal	1 U, x 19 in x 245 mm	48 x LC	OS2	3 kg	1 pc.
41549800ZY	Splice box OV-S 6xLCD/APC, OS2	grigio chiaro	6	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	12 x LC/APC	OS2	1 kg	1 pc.
41544200ZY	Splice box OV-S 12xLCD/APC, OS2	grigio chiaro	12	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	24 x LC/APC	OS2	2,7 kg	1 pc.
41544300ZY	Splice box OV-S 24xLCD/APC, OS2	grigio chiaro	24	LCD/APC	verde	offset horizontal	1 U, x 19 in x 245 mm	48 x LC/APC	OS2	2,7 kg	1 pc.
41545400ZY	Splice box OV-S 12xLCQ, OS2	nera	12	LCQ	blu	angled	1 U, x 19 in x 245 mm	48 x LC	OS2	2,5 kg	1 pc.
41540400ZY	Splice box OV-S 12xLCQ, OS2	grigio chiaro	12	LCQ	blu	vertical	1 U, x 19 in x 245 mm	48 x LC	OS2	3,3 kg	1 pc.
41533100ZY	Splice box OV-S 24xLCQ, OS2	nera	24	LCQ	blu	vertical	1 U, x 19 in x 245 mm	96 x LC	OS2	3,3 kg	1 pc.
41527500ZY	Splice box OV-S 24xLCQ, OS2	grigio chiaro	24	LCQ	blu	vertical	1 U, x 19 in x 245 mm	96 x LC	OS2	3,3 kg	1 pc.
41537200ZY	Splice box OV-S 6xLSH/APC, OS2	nera	6	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	6 x LSH/APC	OS2	2,3 kg	1 pc.
41531300ZY	Splice box OV-S 6xLSH/APC, OS2	grigio chiaro	6	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	6 x LSH/APC	OS2	2,5 kg	1 pc.
41537500ZY	Splice box OV-S 12xLSH/APC, OS2	nera	12	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	12 x LSH/APC	OS2	2,6 kg	1 pc.
41531500ZY	Splice box OV-S 12xLSH/APC, OS2	grigio chiaro	12	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	12 x LSH/APC	OS2	2,5 kg	1 pc.
41537800ZY	Splice box OV-S 24xLSH/APC, OS2	nera	24	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	24 x LSH/APC	OS2	2,8 kg	1 pc.
41531700ZY	Splice box OV-S 24xLSH/APC, OS2	grigio chiaro	24	LSH/APC	verde	vertical	1 U, x 19 in x 245 mm	24 x LSH/APC	OS2	2,8 kg	1 pc.
41548700ZY	Splice box OV-S 6xLSH-C/APC, OS2	grigio chiaro	6	LSH-C/APC	verde	vertical	1 U, x 19 in x 245 mm	12 x LSH/APC	OS2	2,6 kg	1 pc.
41538500ZY	Splice box OV-S 12xLSH-C/APC, OS2	grigio chiaro	12	LSH-C/APC	verde	vertical	1 U, x 19 in x 245 mm	24 x LSH/APC	OS2	2,8 kg	1 pc.
41538400ZY	Splice box OV-S 24xLSH-C/APC, OS2	grigio chiaro	24	LSH-C/APC	verde	vertical	1 U, x 19 in x 245 mm	48 x LSH/APC	OS2	2,8 kg	1 pc.
41547000ZY	Splice box OV-S 2xSCD, OS2	grigio chiaro	2	SCD	blu	vertical	1 U, x 19 in x 245 mm	4 x SC	OS2	2,8 kg	1 pc.
41547100ZY	Splice box OV-S 4xSCD, OS2	grigio chiaro	4	SCD	blu	vertical	1 U, x 19 in x 245 mm	8 x SC	OS2	2,8 kg	1 pc.
41536400ZY	Splice box OV-S 6xSCD, OS2	nera	6	SCD	blu	vertical	1 U, x 19 in x 245 mm	12 x SC	OS2	2,8 kg	1 pc.



Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
41522200ZY	Splice box OV-S 6xSCD, OS2	grigio chiaro	6	SCD	blu	vertical	1 U, x 19 in x 245 mm	12 x SC	OS2	3 kg	1 pc.
41538700ZY	Splice box OV-S 12xSCD, OS2	nera	12	SCD	blu	vertical	1 U, x 19 in x 245 mm	24 x SC	OS2	2,7 kg	1 pc.
41522600ZY	Splice box OV-S 12xSCD, OS2	grigio chiaro	12	SCD	blu	vertical	1 U, x 19 in x 245 mm	24 x SC	OS2	3 kg	1 pc.
41541200ZY	Splice box OV-S 12xSCD, OS2	grigio chiaro	12	SCD	metal	vertical	1 U, x 19 in x 245 mm	24 x SC	OS2	3 kg	1 pc.
41538800ZY	Splice box OV-S 24xSCD, OS2	nera	24	SCD	blu	vertical	1 U, x 19 in x 245 mm	48 x SC	OS2	3 kg	1 pc.
41523000ZY	Splice box OV-S 24xSCD, OS2	grigio chiaro	24	SCD	blu	vertical	1 U, x 19 in x 245 mm	48 x SC	OS2	3 kg	1 pc.
41541300ZY	Splice box OV-S 24xSCD, OS2	grigio chiaro	24	SCD	metal	vertical	1 U, x 19 in x 245 mm	48 x SC	OS2	3 kg	1 pc.
41888700ZY	Splice box OV-S 12xSCD/APC, OS2	grigio chiaro	12	SCD/APC	verde	vertical	1 U, x 19 in x 245 mm	24 x SC/APC	OS2	2,8 kg	1 pc.
41888600ZY	Splice box OV-S 24xSCD/APC, OS2	grigio chiaro	24	SCD/APC	verde	vertical	1 U, x 19 in x 245 mm	48 x SC/APC	OS2	2,8 kg	1 pc.
41534400ZY	Splice box OV-S 6xST, OS2	nera	6	ST	metal	vertical	1 U, x 19 in x 245 mm	6 x ST	OS2	2,8 kg	1 pc.
41523400ZY	Splice box OV-S 6xST, OS2	grigio chiaro	6	ST	metal	vertical	1 U, x 19 in x 245 mm	6 x ST	OS2	2,8 kg	1 pc.
41535100ZY	Splice box OV-S 12xST, OS2	nera	12	ST	metal	vertical	1 U, x 19 in x 245 mm	12 x ST	OS2	2,5 kg	1 pc.
41523800ZY	Splice box OV-S 12xST, OS2	grigio chiaro	12	ST	metal	vertical	1 U, x 19 in x 245 mm	12 x ST	OS2	2,5 kg	1 pc.
41535400ZY	Splice box OV-S 24xST, OS2	nera	24	ST	metal	vertical	1 U, x 19 in x 245 mm	24 x ST	OS2	2,5 kg	1 pc.
41524200ZY	Splice box OV-S 24xST, OS2	grigio chiaro	24	ST	metal	vertical	1 U, x 19 in x 245 mm	24 x ST	OS2	2,5 kg	1 pc.

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-05-07 10:19:09