

FO patch panel OV-S

19"/1U, Breakout box OV-S, G50/125 OM3

with adapters



Breakout box OV-S, 19"/1U, extractable, configuration example with 6 SCD adapters

Description

For the termination of pre-assembled fibre optic cables - maximum of 96 fibres.
Loaded with a maximum of 12 / 24 FO adapters.

Proprietà generali

Alloggiamento	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Capacità	up to 96 fibres
Dimensioni	19"/1U
Impronta	numbers (silk screen printing) on frontplate
Ingresso cavi	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Piastra frontale	similar to RAL 7035, similar to RAL 9005 or stainless steel
Scarico della trazione	with cable tie and screwed cable gland (M20)

Proprietà ottiche

Tipologia di fibra	G50/125 OM3
--------------------	-------------

Proprietà meccaniche

Adattatore	SCD, LCD, LCQ, LSH Coloured Polymer housings or ST metal housings, ceramic sleeves
------------	--

Scope of delivery

Breakout box with
- two straight cable entries
- FO adapters, fastened by screws

Versions

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Classe della fibra	Peso [kg]	Packing unit
41542600ZY	Breakout box OV-S 6xLCD, OM3	nera	6	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.
41525200ZY	Breakout box OV-S 6xLCD, OM3	grigio chiaro	6	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Classe della fibra	Peso [kg]	Packing unit
41542800ZY	Breakout box OV-S 12xLCD, OM3	nera	12	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.
41545000ZY	Breakout box OV-S 12xLCD, OM3	nera	12	LCD	turchese	angled	1 U, x 19 in x 245 mm	OM3	2 kg	1 pc.
41525600ZY	Breakout box OV-S 12xLCD, OM3	grigio chiaro	12	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.
41543000ZY	Breakout box OV-S 24xLCD, OM3	nera	24	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.
41526000ZY	Breakout box OV-S 24xLCD, OM3	grigio chiaro	24	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	OM3	2,6 kg	1 pc.
41545600ZY	Breakout box OV-S 12xLCQ, OM3	nera	12	LCQ	turchese	angled	1 U, x 19 in x 245 mm	OM3	2 kg	1 pc.
41528000ZY	Breakout box OV-S 24xLCQ, OM3	grigio chiaro	24	LCQ	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,8 kg	1 pc.
41543200ZY	Breakout box OV-S 6xSCD, OM3	nera	6	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,4 kg	1 pc.
41526400ZY	Breakout box OV-S 6xSCD, OM3	grigio chiaro	6	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,4 kg	1 pc.
41533500ZY	Breakout box OV-S 12xSCD, OM3	nera	12	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,7 kg	1 pc.
41526800ZY	Breakout box OV-S 12xSCD, OM3	grigio chiaro	12	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,7 kg	1 pc.
41543500ZY	Breakout box OV-S 24xSCD, OM3	nera	24	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,8 kg	1 pc.
41527200ZY	Breakout box OV-S 24xSCD, OM3	grigio chiaro	24	SCD	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,8 kg	1 pc.
41530400ZY	Breakout box OV-S 6xLSH, OM3	grigio chiaro	6	LSH	turchese	vertical	1 U, x 19 in x 245 mm	OM3	2,8 kg	1 pc.

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-05-07 10:19:10