

## HD-DCS modular panels, 19"/1U

to take 4 or 12 HD-DCS plug-in modules



### Beschrijving

Sturdy stainless steel housing with depth-adjustable cable support plate and front 19"/1U mounting brackets.

Pre-assembled with four slots to take HD-DCS plug-in modules from the front or rear. Each slot accepts three plug-in modules with 6 ports or one plug-in module with 12 or 24 ports.

Allows for variable, scalable port densities from 48 up to 96 ports (LCD and MPO/MTP<sup>®</sup>).

### Toepassing

Modular, scalable high-density platform for the data centre environment.

Variable port densities of up to 96 LCD and/or MPO ports on one rack unit (U). This allows for up to 192 fibres (with LCD) or 1152 fibres (with MPO<sub>12</sub>) per height unit.

### Algemene eigenschappen

Capaciteit

12 plug-in modules with 6 LCD or MPO ports  
 4 plug-in modules with 12 LCD or MPO ports  
 4 plug-in modules with 24 LCD or MPO ports

### Leveringsomvang

19"/1U panel (19" mounting brackets) with integrated, depth-adjustable cable support plate (without plug-in modules)

2 cover plates with label strips

19" mounting material

Accessories such as strain relief clips and cable mounting clips to be ordered separately.

### Versions

Materiaal nummer	Artikel	Kleur (Frontplate)	Buitenste afmetingen	Kleur	Gewicht [kg]	Verpakkingseenheid
473600	HD-DCS panel 19" 1U, 4x 12/24-port	zwart	1 U44.2 mm x 483 mm x 432.1 mm	zilver	2,25 kg	1 stk.
473601	HD-DCS panel 19" 1U, 12x 6-port	zwart	1 U44.2 mm x 483 mm x 432.1 mm	zilver	2,25 kg	1 stk.
473602	HD-DCS panel 19" 1U, 6/12/24-port	zwart	1 U44.2 mm x 483 mm x 432.1 mm	zilver	2,25 kg	1 stk.

MTP<sup>®</sup> is a registered trade name of US Conec.