

# DIN rail splice distribution box

G50/125 OM4

with adapters and pigtails



DIN rail splice distribution box, loaded with 6 LCD adapters

## Description

For the termination of fibre optic cables in control cabinets and distribution boxes - maximum of 24 fibres.  
 For mounting on support or top-hat rail (DIN rail TH35).  
 Top-hat rail fastening mounted centrally, possibility of asymmetrical fastening.  
 Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

## General Properties

Colour	similar to RAL 7035
Dimensions	135 x 38 x 141 mm
Outer dimensions (HxWxD)	38 mm x 135 mm x 141 mm
Housing	aluminium
Imprint	label strips
Cable entry	two cable entry openings and one M20 gland
Strain relief	by screwed cable gland
Capacity	up to 24 fibres

## Optical Properties

Adapter	LCD, LCQ, LSH or SCD with ceramic sleeves
Fibre class	Multimode
Fibre type	G50/125
Fibre category	OM4
Colour code	IEC 60304
Adapter colour	heather violet
Ferrule material	Zirconia

## Scope of delivery

- DIN rail splice distribution box
- straight cable entry (right and left or rear)
  - splice tray
  - FO adapters, fastened by screws
  - complete splicing set with crimp splice protection
  - labelling strip
  - cable gland (1x M20)

## Note

Wall mounting is possible with additional mounting brackets.

## Versions

Material number	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Pigtails	Fibre class	Weight [kg]	Packing unit	GTIN / EAN
415631	DIN rail splice distribution box	grey	6	LCD	heather violet	12x LC	OM4	0.35 kg	1 pc.	40393910173130
415632	DIN rail splice distribution box	grey	6	SCD	heather violet	12x SC	OM4	0.35 kg	1 pc.	40393910173123
415636	DIN rail splice distribution box	grey	6	LCQ	heather violet	24x LC	OM4	0.35 kg	1 pc.	40393910173086

Variants on request.

Subject to technical modification

As of 2023-01-13 07:57:52