

## HD-DCS BO module, 24x LCD/PC, OS2

for HD-DCS modular panels



### Beschrijving

Polycarbonate (PC) housing with press-fit cover.  
At the rear the HD-DCS BO modules have a slot fitted with a cable grommet.  
Front couplers with integrated, automatic transparent dust shutters.

### Toepassing

HD-DCS BO modules are suitable for all high-density and high-performance applications with duplex signals, particularly in the data centre environment.

They find modular application in the slots of the HD-DCS modular panels (19"/1U) in which they can be inserted from the front and the back.

They are used to accept pre-assembled LC/LCD trunk cables.

A packing density of 192 fibres on 1U are achieved with these type of modules.

### Algemene eigenschappen

Acceptatie capaciteit	48 vezels
-----------------------	-----------

### Optische eigenschappen

Aantal adapters, voorzijde	4
Adapter, voorkant	4 x 6LCD, blauw (Inner shutter, translucent)
Adapter colour, front side	blauw
Adapter material, front side	Polymerisch
Mouwmetaal, voorkant	Zirkonia (ZrO <sub>2</sub> )
Type adapter, voorkant	6LCD

### Mechanische eigenschappen

Laserbescherming, voorzijde	No
Stof- / laserbescherming, voorzijde	Inner shutter, translucent
Stofbescherming, voorzijde	Yes

### Leveringsomvang

Housing, equipped with 4x 6LCD adapter with ceramic sleeves and translucent inner shutter on front side.  
Rear side is fitted with a cable grommet.

### Normen / Standards

LC standard (IEC)	IEC 61754-20
-------------------	--------------

### Noot

As high-performance patch cables for high-density solutions Datwyler recommends the HD-DCS LCD Uniboot patch cables with push-pull rods.

## Versions

Materiaal nummer	Artikel	Buitenste afmetingen	Kleur	Materiaal	Gewicht [kg]	Verpakkingseenheid
473545	HD-DCS BO module, 24x LCD/ PC, OS2	39 mm x 100 mm x 120 mm	zwart	Polycarbonaat (PC)	0,19 kg	1 stk.

Onder voorbehoud van technische wijziging

Vanaf 2021-01-22 11:00:46