

HD-DCS BO module, 12x LCD/PC, OM4

for HD-DCS modular panels



Beschrijving

Polycarbonate (PC) housing with press-fit cover.
At the rear the HD-DCS BO modules have a slot fitted with a cable grommet.
Front couplers with integrated, automatic transparent dust shutters.

Toepassing

HD-DCS BO modules are suitable for all high-density and high-performance applications with duplex signals, particularly in the data centre environment.

They find modular application in the slots of the HD-DCS modular panels (19"/1U) in which they can be inserted from the front and the back.

They are used to accept pre-assembled LC/LCD trunk cables.

A packing density of 96 fibres on 1U are achieved with these type of modules.

Algemene eigenschappen

Acceptatie capaciteit	24 vezels
-----------------------	-----------

Optische eigenschappen

Aantal adapters, voorzijde	2
Adapter, voorkant	2 x 6LCD, heidepaars (Inner shutter, translucent)
Adapter colour, front side	heidepaars
Adapter material, front side	Polymerisch
Mouwmetaal, voorkant	Zirkonia (ZrO ₂)
Type adapter, voorkant	6LCD

Mechanische eigenschappen

Laserbescherming, voorzijde	No
Stof- / laserbescherming, voorzijde	Inner shutter, translucent
Stofbescherming, voorzijde	Yes

Leveringsomvang

Housing, equipped with 2x 6LCD adapter with ceramic sleeves and translucent inner shutter on front side.
Rear side is fitted with a cable grommet.

Normen / Standards

LC standard (IEC)	IEC 61754-20
-------------------	--------------

Noot

As high-performance patch cables for high-density solutions Datwyler recommends the HD-DCS LCD Uniboot patch cables with push-pull rods.

Versions

Materiaal nummer	Artikel	Buitenste afmetingen	Kleur	Materiaal	Gewicht [kg]	Verpakkingseenheid
473540	HD-DCS BO module, 12x LCD/ PC, OM4	39 mm x 100 mm x 120 mm	zwart	Polycarbonaat (PC)	0,11 kg	1 stk.

Onder voorbehoud van technische wijziging

Vanaf 2021-01-22 11:00:38