

FO patch panel OV-S

19"/1U, Splice box OV-S, G50/125 OM3, with crimp splice protectors with adapters and pigtails



Fibre optic splice box OV-S, 19"/1U, extractable, configuration example with 24 SCD adapters and 48 pigtails

Description

For the termination of fibre optic cables - maximum of 96 fibres.
Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

Proprietà generali

Alloggiamento	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Capacità	up to 96 fibres
Dimensioni	19"/1U
Impronta	numbers (silk screen printing) on frontplate
Ingresso cavi	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Piastra frontale	similar to RAL 7035, similar to RAL 9005 or stainless steel
Scarico della trazione	with screwed cable gland

Proprietà ottiche

Tipologia di fibra	G50/125 OM3
--------------------	-------------

Proprietà meccaniche

Adattatore	SCD, LCD, LCQ, LSH Coloured Polymer housings or ST metal housings, ceramic sleeves
------------	------------------------------------------------------------------------------------

Scope of delivery

- Splice box with
- two straight cable entries
- one screwed cable gland M20
- coloured pigtails with measurement report
- FO adapters, fastened by screws
- splice trays with cover
- splice holder for 12 x crimp splice protectors
- Delivery with splicing protection
- mounting kit

Versions

Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
41539003ZY	Splice box OV-S 2xLCD, OM3	grigio chiaro	2	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	4 x LC	OM3	2,5 kg	1 pc.



Numero Materiale	Product	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
41546903ZY	Splice box OV-S 4xLCD, OM3	grigio chiaro	4	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	8 x LC	OM3	3 kg	1 pc.
41533603ZY	Splice box OV-S 6xLCD, OM3	nera	6	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	12 x LC	OM3	2,5 kg	1 pc.
41521203ZY	Splice box OV-S 6xLCD, OM3	grigio chiaro	6	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	12 x LC	OM3	3 kg	1 pc.
41535903ZY	Splice box OV-S 12xLCD, OM3	nera	12	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	24 x LC	OM3	3,1 kg	1 pc.
41521603ZY	Splice box OV-S 12xLCD, OM3	grigio chiaro	12	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	24 x LC	OM3	3 kg	1 pc.
41536103ZY	Splice box OV-S 24xLCD, OM3	nera	24	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	48 x LC	OM3	2,8 kg	1 pc.
41518103ZY	Splice box OV-S 24xLCD, OM3	nera	24	LCD	turchese	vertical	1 U, x 19 in x 245 mm	48 x LC	OM3	3,56 kg	1 pc.
41522003ZY	Splice box OV-S 24xLCD, OM3	grigio chiaro	24	LCD	turchese	offset horizontal	1 U, x 19 in x 245 mm	48 x LC	OM3	3,56 kg	1 pc.
41531403ZY	Splice box OV-S 6xLSH, OM3	grigio chiaro	6	LSH	turchese	vertical	1 U, x 19 in x 245 mm	6 x LSH	OM3	2,3 kg	1 pc.
41531603ZY	Splice box OV-S 12xLSH, OM3	grigio chiaro	12	LSH	turchese	vertical	1 U, x 19 in x 245 mm	12 x LSH	OM3	2,6 kg	1 pc.
41531803ZY	Splice box OV-S 24xLSH, OM3	grigio chiaro	24	LSH	turchese	vertical	1 U, x 19 in x 245 mm	24 x LSH	OM3	2,8 kg	1 pc.
41541403ZY	Splice box OV-S 12xLSH-C, OM3	grigio chiaro	12	LSH-C	turchese	vertical	1 U, x 19 in x 245 mm	24 x LSH	OM3	2,8 kg	1 pc.
41522403ZY	Splice box OV-S 6xSCD, OM3	grigio chiaro	6	SCD	turchese	vertical	1 U, x 19 in x 245 mm	12 x SC	OM3	3 kg	1 pc.
41522803ZY	Splice box OV-S 12xSCD, OM3	grigio chiaro	12	SCD	turchese	vertical	1 U, x 19 in x 245 mm	24 x SC	OM3	3 kg	1 pc.
41523203ZY	Splice box OV-S 24xSCD, OM3	grigio chiaro	24	SCD	turchese	vertical	1 U, x 19 in x 245 mm	48 x SC	OM3	3 kg	1 pc.
41524003ZY	Splice box OV-S 12xST, OM3	grigio chiaro	12	ST	metal	vertical	1 U, x 19 in x 245 mm	12 x ST	OM3	2,5 kg	1 pc.

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-05-07 10:19:09