

FO patch panel OV-S (VW), long version

19"/1U and 2U, Splice box OV-S, E9/125 G.652.D OS2

with adapters and pigtails



Fibre optic splice box OV-S, 19"/1U, extractable, configuration example with 24 LCD/APC adapters and 48 pigtails

Descrizione

For the termination of fibre optic cables - maximum of 96 fibres.
Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: IEC 60304).

Proprietà generali

Alloggiamento	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Capacità	up to 48 fibres
Dimensioni	19"/1U and 2U
Impronta	numbers (silk screen printing) on frontplate
Ingresso cavi	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Piastra frontale	similar to RAL 7035
Profondità	300 mm
Scarico della trazione	with screwed cable gland

Proprietà ottiche

Tipologia di fibra	E9/125 G.652.D OS2
--------------------	--------------------

Proprietà meccaniche

Adattatore	LCD, SCD or LSH Coloured Polymer housings, ceramic sleeves
------------	--

Ambito di consegna

- Splice box with
- two straight cable entries
 - one angled cable entry enclosed
 - one cable gland M20
 - coloured pigtails with measurement report
 - FO adapters, fastened by screws
 - splice trays with cover
 - splice holder for 12 x crimp splice protectors
 - Delivery with splicing protection

Versioni



Codice art.	Prodotto	Colour (Front-plate)	Number of adapters	Adapter	Colour (Adapter)	Orientamento adattatore	Dimensioni esterne	Pigtails	Classe della fibra	Peso [kg]	Packing unit
415522	Splice box OV-S 12xLCD, OS2	grigio chiaro	12	LCD	blu	offset horizontal	1 U, x 19 in x 300 mm	24 x LC	OS2	2,5 kg	1 pc.
415514	Splice box OV-S 24xLCD, OS2	grigio chiaro	24	LCD	blu	offset horizontal	1 U, x 19 in x 300 mm	48 x LC	OS2	3,3 kg	1 pc.
415511	Splice box OV-S 12xLCD/APC, OS2	grigio chiaro	12	LCD/APC	verde	offset horizontal	1 U, x 19 in x 300 mm	24 x LC/APC	OS2	2,8 kg	1 pc.
415521	Splice box OV-S 24xLCD/APC, OS2	grigio chiaro	24	LCD/APC	verde	offset horizontal	1 U, x 19 in x 300 mm	48 x LC/APC	OS2	3,3 kg	1 pc.
415517	Splice box OV-S 12xLSH/APC, OS2	grigio chiaro	12	LSH/APC	verde	vertical	1 U, x 19 in x 300 mm	12 x LSH/APC	OS2	2,7 kg	1 pc.
415518	Splice box OV-S 24xLSH/APC, OS2	grigio chiaro	24	LSH/APC	verde	vertical	1 U, x 19 in x 300 mm	24 x LSH/APC	OS2	2,9 kg	1 pc.
415515	Splice box OV-S 12xSCD, OS2	grigio chiaro	12	SCD	blu	horizontal	1 U, x 19 in x 300 mm	24 x SC	OS2	3 kg	1 pc.
415516	Splice box OV-S 24xSCD, OS2	grigio chiaro	24	SCD	blu	horizontal	2 U, x 19 in x 300 mm	48 x SC	OS2	3,7 kg	1 pc.

Variants on request.

Con riserva di modifiche tecniche

A partire da 2021-06-11 12:13:42