

Fibre pigtail 2m

E9/125 G.652.D OS2, PC Version



Description

Semi tight buffer, 900 µm
 Colours single pigtails: yellow
 Colours sets of pigtails: in accordance with IEC 60304

Optical Properties

Connector grade (better than)	B2
Ferrule material	Zirkonia
Fibre type	E9/125 G.652.D OS2
Insertion loss (IL), maximal	0.25 dB
Insertion loss (IL), typical	0.12 dB
Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	50 dB
Return loss (RL), typical	55 dB

Versions

Material number	Product	Fibre type	Connector type	Weight [kg]	Packing unit
421121	Fibre Pigtail	E9/125 G.652.D OS2	SC	0.01 kg	1 pc.
421122	Fibre Pigtail	E9/125 G.652.D OS2	SC	0.07 kg	1 set
422221	Fibre Pigtail	E9/125 G.652.D OS2	ST	0.1 kg	1 pc.
422222	Fibre Pigtail	E9/125 G.652.D OS2	ST	0.08 kg	1 set
423321	Fibre Pigtail	E9/125 G.652.D OS2	LC	0.01 kg	1 pc.
423322	Fibre Pigtail	E9/125 G.652.D OS2	LC	0.1 kg	1 set
424421	Fibre Pigtail	E9/125 G.652.D OS2	LSH	0.01 kg	1 pc.
424422	Fibre Pigtail	E9/125 G.652.D OS2	LSH	0.1 kg	1 set
425521	Fibre Pigtail	E9/125 G.652.D OS2	FC/PC	0.1 kg	1 pc.
425522	Fibre Pigtail	E9/125 G.652.D OS2	FC/PC	0.1 kg	1 set