

## Fibre pigtail 2m

E9/125 G.652.D OS2, PC Version



### Description

Semi tight buffer, 900 µm  
 Colours single pigtails: yellow  
 Colours sets of pigtails: in accordance with IEC 60304

### Proprietà ottiche

Durata della vita	1000 connections with stable attenuation values
Insertion loss (IL), maximal	0,25 dB
Insertion loss (IL), typical	0,12 dB
Materiale ghiera	Zirkonia
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	50 dB
Return loss (RL), typical	55 dB
Tipo di connettore (migliore di)	B2
Tipologia di fibra	E9/125 G.652.D OS2

### Versions

Numero Materiale	Product	Fibre type	Tipologia di connettore	Peso [kg]	Packing unit
421121	Fibre Pigtail	E9/125 G.652.D OS2	SC	0,01 kg	1 pc.
421122	Fibre Pigtail	E9/125 G.652.D OS2	SC	0,07 kg	1 kit
422221	Fibre Pigtail	E9/125 G.652.D OS2	ST	0,1 kg	1 pc.
422222	Fibre Pigtail	E9/125 G.652.D OS2	ST	0,08 kg	1 kit
423321	Fibre Pigtail	E9/125 G.652.D OS2	LC	0,01 kg	1 pc.
423322	Fibre Pigtail	E9/125 G.652.D OS2	LC	0,1 kg	1 kit
424421	Fibre Pigtail	E9/125 G.652.D OS2	LSH	0,01 kg	1 pc.
424422	Fibre Pigtail	E9/125 G.652.D OS2	LSH	0,1 kg	1 kit
425521	Fibre Pigtail	E9/125 G.652.D OS2	FC/PC	0,1 kg	1 pc.
425522	Fibre Pigtail	E9/125 G.652.D OS2	FC/PC	0,1 kg	1 kit