

## Fibre pigtail 2m

E9/125 G.652.D OS2, APC Version



### Description

Semi tight buffer, 900 µm  
 Colours single pigtails: yellow  
 Colours sets of pigtails: in accordance with IEC 60304

### Optical Properties

|                               |   |
|-------------------------------|---|
| Connector grade (better than) | B1  |
| Ferrule material              | Zirkonia  |
| Fibre type                    | E9/125 G.652.D OS2                              |
| Insertion loss (IL), maximal  | 0.25 dB   |
| Insertion loss (IL), typical  | 0.12 dB   |
| Lifetime                      | 1000 connections with stable attenuation values |
| Reproducibility of the IL     | maximal +/- 0.1dB                               |
| Return loss (RL), minimal     | 65 dB   |
| Return loss (RL), typical     | 70 dB   |

### Versions

| Material number | Product       | Fibre type         | Connector type | Weight [kg] | Packing unit |
|-----------------|---------------|--------------------|----------------|-------------|--------------|
| 427721          | Fibre Pigtail | E9/125 G.652.D OS2 | SC/APC         | 0.1 kg      | 1 pc.        |
| 427722          | Fibre Pigtail | E9/125 G.652.D OS2 | SC/APC         | 0.07 kg     | 1 set        |
| 429921          | Fibre Pigtail | E9/125 G.652.D OS2 | LC/APC         | 0.1 kg      | 1 pc.        |
| 429922          | Fibre Pigtail | E9/125 G.652.D OS2 | LC/APC         | 0.04 kg     | 1 set        |
| 428821          | Fibre Pigtail | E9/125 G.652.D OS2 | LSH/APC        | 0.01 kg     | 1 pc.        |
| 309631          | Fibre Pigtail | E9/125 G.652.D OS2 | LSH/APC        | 0.05 kg     | 1 set        |