

Fibre pigtail 2m

E9/125 G.652.D OS2, APC Version



Description

Semi tight buffer, 900 µm
 Colours single pigtails: yellow
 Colours sets of pigtails: in accordance with IEC 60304

Proprietà ottiche

Durata della vita	1000 connections with stable attenuation values
Insertion loss (IL), maximal	0,25 dB
Insertion loss (IL), typical	0,12 dB
Materiale ghiera	Zirkonia
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	65 dB
Return loss (RL), typical	70 dB
Tipo di connettore (migliore di)	B1
Tipologia di fibra	E9/125 G.652.D OS2

Versions

Numero Materiale	Product	Fibre type	Tipologia di connettore	Peso [kg]	Packing unit
427721	Fibre Pigtail	E9/125 G.652.D OS2	SC/APC	0,1 kg	1 pc.
427722	Fibre Pigtail	E9/125 G.652.D OS2	SC/APC	0,07 kg	1 kit
429921	Fibre Pigtail	E9/125 G.652.D OS2	LC/APC	0,1 kg	1 pc.
429922	Fibre Pigtail	E9/125 G.652.D OS2	LC/APC	0,04 kg	1 kit
428821	Fibre Pigtail	E9/125 G.652.D OS2	LSH/APC	0,01 kg	1 pc.
309631	Fibre Pigtail	E9/125 G.652.D OS2	LSH/APC	0,05 kg	1 kit