

## Fibre pigtail 2m

G50/125 OM2



### Description

Semi tight buffer, 900 µm  
 Colours single pigtails: orange  
 Colours sets of pigtails: in accordance with IEC 60304

### Proprietà ottiche

Durata della vita	1000 connections with stable attenuation values
Insertion loss (IL), maximal	0,3 dB
Insertion loss (IL), typical	0,15 dB
Materiale ghiera	Zirkonia
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	30 dB
Return loss (RL), typical	35 dB
Tipo di connettore (migliore di)	Bm2m
Tipologia di fibra	G50/125 OM2

### Versions

Numero Materiale	Product	Fibre type	Tipologia di connettore	Peso [kg]	Packing unit
421161	Fibre Pigtail	G50/125 OM2	SC	0,01 kg	1 pc.
421162	Fibre Pigtail	G50/125 OM2	SC	0,07 kg	1 kit
422261	Fibre Pigtail	G50/125 OM2	ST	0,01 kg	1 pc.
422262	Fibre Pigtail	G50/125 OM2	ST	0,08 kg	1 kit
423361	Fibre Pigtail	G50/125 OM2	LC	0,01 kg	1 pc.
423362	Fibre Pigtail	G50/125 OM2	LC	0,04 kg	1 kit
424461	Fibre Pigtail	G50/125 OM2	LSH	0,01 kg	1 pc.
424462	Fibre Pigtail	G50/125 OM2	LSH	0,1 kg	1 kit
425561	Fibre Pigtail	G50/125 OM2	FC/PC	0,1 kg	1 pc.
425562	Fibre Pigtail	G50/125 OM2	FC/PC	0,1 kg	1 kit