

Fibre pigtail 2m

G50/125 OM3



Description

Semi tight buffer, 900 µm

Colours single pigtails: turquoise

Colours sets of pigtails: in accordance with IEC 60304

Optical Properties

Connector grade (better than)	Bm2m
Ferrule material	Zirkonia
Fibre type	G50/125 OM3
Insertion loss (IL), maximal	0.3 dB
Insertion loss (IL), typical	0.15 dB
Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	30 dB
Return loss (RL), typical	35 dB

Versions

Material number	Product	Fibre type	Connector type	Weight [kg]	Packing unit
421141	Fibre Pigtail	G50/125 OM3	SC	0.01 kg	1 pc.
421142	Fibre Pigtail	G50/125 OM3	SC	0.1 kg	1 set
422242	Fibre Pigtail	G50/125 OM3	ST	0.08 kg	1 set
422241	Fibre Pigtail	G50/125 OM3	ST	0 kg	1 pc.
423341	Fibre Pigtail	G50/125 OM3	LC	0.01 kg	1 pc.
423342	Fibre Pigtail	G50/125 OM3	LC	0.04 kg	1 set
424441	Fibre Pigtail	G50/125 OM3	LSH	0.01 kg	1 pc.
424442	Fibre Pigtail	G50/125 OM3	LSH	0.05 kg	1 set
425541	Fibre Pigtail	G50/125 OM3	FC/PC	0.1 kg	1 pc.
425542	Fibre Pigtail	G50/125 OM3	FC/PC	0.1 kg	1 set