

Fibre pigtail 2m

G50/125 OM3



Description

Semi tight buffer, 900 µm
 Colours single pigtails: turquoise
 Colours sets of pigtails: in accordance with IEC 60304

Proprietà ottiche

Durata della vita	1000 connections with stable attenuation values
Insertion loss (IL), maximal	0,3 dB
Insertion loss (IL), typical	0,15 dB
Materiale ghiera	Zirkonia
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	30 dB
Return loss (RL), typical	35 dB
Tipo di connettore (migliore di)	Bm2m
Tipologia di fibra	G50/125 OM3

Versions

Numero Materiale	Product	Fibre type	Tipologia di connettore	Peso [kg]	Packing unit
421141	Fibre Pigtail	G50/125 OM3	SC	0,01 kg	1 pc.
421142	Fibre Pigtail	G50/125 OM3	SC	0,1 kg	1 kit
422242	Fibre Pigtail	G50/125 OM3	ST	0,08 kg	1 kit
422241	Fibre Pigtail	G50/125 OM3	ST	0 kg	1 pc.
423341	Fibre Pigtail	G50/125 OM3	LC	0,01 kg	1 pc.
423342	Fibre Pigtail	G50/125 OM3	LC	0,04 kg	1 kit
424441	Fibre Pigtail	G50/125 OM3	LSH	0,01 kg	1 pc.
424442	Fibre Pigtail	G50/125 OM3	LSH	0,05 kg	1 kit
425541	Fibre Pigtail	G50/125 OM3	FC/PC	0,1 kg	1 pc.
425542	Fibre Pigtail	G50/125 OM3	FC/PC	0,1 kg	1 kit