

Fibre pigtail 2m

G50/125 OM4



Description

Semi tight buffer, 900 µm

Colours single pigtails: heather violet

Colours sets of pigtails: in accordance with IEC 60304

Optical Properties

Connector grade (better than)	Bm2m
Ferrule material	Zirkonia
Fibre type	G50/125 OM4
Insertion loss (IL), maximal	0.3 dB
Insertion loss (IL), typical	0.15 dB
Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	30 dB
Return loss (RL), typical	35 dB

Versions

Material number	Product	Fibre type	Connector type	Weight [kg]	Packing unit
421144	Fibre Pigtail	G50/125 OM4	SC	0.05 kg	1 pc.
421145	Fibre Pigtail	G50/125 OM4	SC	0.07 kg	1 set
422244	Fibre Pigtail	G50/125 OM4	ST	0.05 kg	1 pc.
422245	Fibre Pigtail	G50/125 OM4	ST	0.05 kg	1 set
423348	Fibre Pigtail	G50/125 OM4	LC	0.01 kg	1 pc.
423349	Fibre Pigtail	G50/125 OM4	LC	0.04 kg	1 set
424444	Fibre Pigtail	G50/125 OM4	LSH	0.1 kg	1 pc.