

## Fibre pigtail 2m

G50/125 OM4



### Description

Semi tight buffer, 900 µm

Colours single pigtails: heather violet

Colours sets of pigtails: in accordance with IEC 60304

### Proprietà ottiche

Durata della vita	1000 connections with stable attenuation values
Insertion loss (IL), maximal	0,3 dB
Insertion loss (IL), typical	0,15 dB
Materiale ghiera	Zirkonia
Reproducibility of the IL	maximal +/- 0.1dB
Return loss (RL), minimal	30 dB
Return loss (RL), typical	35 dB
Tipo di connettore (migliore di)	Bm2m
Tipologia di fibra	G50/125 OM4

### Versions

Numero Materiale	Product	Fibre type	Tipologia di connettore	Peso [kg]	Packing unit
421144	Fibre Pigtail	G50/125 OM4	SC	0,05 kg	1 pc.
421145	Fibre Pigtail	G50/125 OM4	SC	0,07 kg	1 kit
422244	Fibre Pigtail	G50/125 OM4	ST	0,05 kg	1 pc.
422245	Fibre Pigtail	G50/125 OM4	ST	0,05 kg	1 kit
423348	Fibre Pigtail	G50/125 OM4	LC	0,01 kg	1 pc.
423349	Fibre Pigtail	G50/125 OM4	LC	0,04 kg	1 kit
424444	Fibre Pigtail	G50/125 OM4	LSH	0,1 kg	1 pc.