

## ODF subracks, Pull-Out

1U, 2U, 3U, 48-144 fibres



High-density subrack for Datwyler ODF, 3U

### Beschrijving

The Datwyler ODF subracks are particularly suitable for high-density applications in telco/carrier networks. They provide advanced splice and patch systems and cable management. Modules are rear mounted for improved side access. Single fibre trays and connected patch cords can slide in and out independently as one pull-out unit. Splice cassette design allows splicing on one side and cable storage on the other side. Folding cassettes (up to 135 degree) for ease of installation and maintenance. Cable glands to secure the incoming fibres. Strain relief for all cables. Bend radius control for fibres.

### Toepassing

Backbone and distribution networks, particularly for PoPs in the carrier section. Also suitable for data centres and LAN projects (19 ).

### Algemene eigenschappen

Capaciteit	24 ports per tray - 1U up to 48, 2U up to 96, 3U up to 144 fibres (72 duplex adapters)
Colour	Light grey, RAL 7035 (powder-coated)

### Versions

Materiaal nummer	Artikel	Antaal Adapters	Adapter	Aantal vezels	Buitenste afmetingen	Gewicht [kg]
19694300ZY	ODF subrack, Pull-Out	24	LCD/APC	48	1U	6,65 kg
19694200ZY	ODF subrack, Pull-Out	48	LCD/APC	96	2U	6,4 kg
19694100ZY	ODF subrack, Pull-Out	72	LCD/APC	144	3U	6,1 kg