

ODF subracks, Easy Access

1U, 2U, 3U, 48-144 fibres



High-density subrack for Datwyler ODF

Description

The Datwyler ODF subracks are particularly suitable for high-density applications in telco/carrier networks. They provide advanced splice and patch systems and cable management. Smooth and convenient telescopic sliding system. Cable glands to secure the incoming fibres. Strain relief for all cables. Bend radius control for fibres.

Impresión de aplicaciones

Backbone and distribution networks, particularly for PoPs in the carrier section. Also suitable for data centres and LAN projects (19).

Propiedades generales

Capacidad	24 ports per tray - 1U up to 48, 2U up to 96, 3U up to 144 fibres (72 duplex adapters)
Colour	Gris claro, RAL 7035 (pulverizado)

Versions

Número de material	Producto	Número de adaptadores	Adaptadores	Número de fibras	Dimensiones exteriores	Peso [kg]
19694600ZY	ODF subrack, Easy Access	24	LCD/APC	48	1U	6,65 kg
19694500ZY	ODF subrack, Easy Access	48	LCD/APC	96	2U	6,4 kg
19694400ZY	ODF subrack, Easy Access	72	LCD/APC	144	3U	6,1 kg

Sujeto a modificaciones técnicas

A partir de 2021-01-20 11:13:37