

## DCS fanout cable MTP-LCDU, 8 fibres OM3

for splitting 100G into 4x 25G or 40G into 4x 10G



DCS fanout cable MTP-LCDU, 8 fibres OM3

### Description

Thin, very flexible fibre-optic fanout cable (round cable, Ø 2.0 mm) with 8 fibres.  
 Low fire load due to its halogen-free flame-retardant LS0H sheath.  
 Available with 2.5 m standard length (other lengths on request).  
 Standard connectivity method can be type A or type C.  
 Sticker labelling at both cable ends.  
 Breakout separation is effected with a thin divider housing.  
 The legs (Ø 2.0 mm) with LCD Uniboot (LCDU) plugs are numbered (1-4).  
 The legs can be ordered graded in length or of equal length.  
 Project-specific assemblies are available on request.

### Application

MTP-on-LCDU fanout cables are suitable for all high-performance applications in a data centre environment.  
 All well-known multimode and single-mode QSFP applications such as SR4, PSM4, PLR4 and FCp can be split into four duplex channels using this cable.  
 The connectivity of this fanout cable splits one 4-channel parallel optic link into four duplex links (e.g. 100G into 4x 25G or 40G into 4x 10G).  
 The fanout cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

### Construction

Outer sheath colour	turquoise
Outer sheath material	FR/LSZH

### Optical Properties

Colour code	IEC 60304
Connector gender side A	Female (unpinned)
Connector type side A	MTP
Connector type side B	LCDU
Ferrule polishing connector A	Elite PC 0°
Ferrule polishing connector B	PC 0°
Fibre type	G50/125 OM3
IL maximal, connector A	0.25 dB
IL maximal, connector B	0.25 dB
IL typical, connector A	0.15 dB
IL typical, connector B	0.15 dB
RL minimal, connector A	35 dB
RL minimal, connector B	35 dB
RL typical, connector A	45 dB
RL typical, connector B	45 dB

## Mechanical properties

Housing colour connector A	aqua
Housing colour connector B	aqua

## Scope of delivery

DCS fanout cable (FR/LS0H) with 8 fibres OM3.  
 High-performance connector assembly with MTP Elite and LCD Uniboot Intelli-Cross Pro.  
 All connectors incl. push-pull tabs.  
 Sticker labelling at both cable ends.

## Standards

LC standard (IEC)	IEC 61754-20
MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Polarity standard	TIA-568-C.3 Type A,B,C
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Flame Propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2

## Note

Insertion Loss (IL) is determined by the latest measurement methods under EFL multimode excitation conditions (EFL = Encircled Flux Launch) at 850 nm in accordance with IEC 61280-4-1.

## Versions

<STEPTABLE O="STEP\_PRODUCT\_478580" OT="Product" TT="267772" VC="CTX\_english" VO="267203" W="Approved" />

MTP® and MTP Elite® are registered brands of US Conec.  
 Intelli-Cross® is a registered trademark of SEIKOH GIKEN Co., Ltd.