


DCS patch cable LCDU/PC, 2 fibres OS2

High-performance



DCS patch cable (FR/LSZH), 2 fibres OS2

Description

Uniboot patch cable with Intelli-Cross® mechanism for fast polarity change.
 Compact cable design with FR/LSOH cable sheath (2.1 mm) and 2 fibres.
 Available in standard lengths up to 10 m.
 Other lengths available on request.
 Connectivity A to A or A to B.
 Sticker labelling at both cable ends.
 Each patch cable is equipped with push-pull tabs.

Application

The LCD to LCD patch cables for are suitable for all high-performance applications with duplex signals in the data center environment. The round patch cables are assembled with LCD Uniboot Intelli-Cross Pro connectors (high-performance) at both ends. The patch cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Construction

Cable	round
Outer sheath colour	yellow
Outer sheath material	FR/LSZH

Optical Properties

Connector type side A	LCDU/PC
Connector type side B	LCDU/PC
Ferrule material	Zirconia
Ferrule polishing connector A	PC 0°
Ferrule polishing connector B	PC 0°
Fibre type	E9/125 G.652.D BLO
IL maximal, connector A	0.25 dB
IL maximal, connector B	0.25 dB
IL typical, connector A	0.1 dB
IL typical, connector B	0.1 dB
RL minimal, connector A	50 dB
RL minimal, connector B	50 dB
RL typical, connector A	55 dB
RL typical, connector B	55 dB

Mechanical properties

Housing colour connector A	blue
Housing colour connector B	blue

Scope of delivery

DCS patch cable (FR/LSOH) with 2 fibres OS2
 High-performance connector assembly with LCD Uniboot Intelli-Cross Pro.
 All connectors incl. push-pull tabs.
 Sticker labelling at both cable ends.

Standards

Zero halogen no corrosive gases	IEC 60754-1/-2
Flame Propagation	IEC 60332-1-2
Flame Spread	IEC 60332-3-22 Cat. A
Smoke Density	IEC 61034-1/-2

Note

Connectivity methods according to TIA-568-C.3 and EN 50174-1

Versions

Material number	Product	Length (m)	Polarity	Weight [kg]	Packing unit
47332000ZY	DCS patch cable LCDU/PC - LCDU/PC	1	A to A	0.02 kg	1 pc.
47332100ZY	DCS patch cable LCDU/PC - LCDU/PC	2	A to A	0.02 kg	1 pc.
47332200ZY	DCS patch cable LCDU/PC - LCDU/PC	3	A to A	0.03 kg	1 pc.
47332300ZY	DCS patch cable LCDU/PC - LCDU/PC	4	A to A	0.03 kg	1 pc.
47332400ZY	DCS patch cable LCDU/PC - LCDU/PC	5	A to A	0.04 kg	1 pc.
47332500ZY	DCS patch cable LCDU/PC - LCDU/PC	6	A to A	0.04 kg	1 pc.
47332600ZY	DCS patch cable LCDU/PC - LCDU/PC	7	A to A	0.04 kg	1 pc.
47332700ZY	DCS patch cable LCDU/PC - LCDU/PC	8	A to A	0.05 kg	1 pc.
47332800ZY	DCS patch cable LCDU/PC - LCDU/PC	9	A to A	0.05 kg	1 pc.
47332900ZY	DCS patch cable LCDU/PC - LCDU/PC	10	A to A	0.06 kg	1 pc.
47330000ZY	DCS patch cable LCDU/PC - LCDU/PC	1	A to B	0.02 kg	1 pc.
47330100ZY	DCS patch cable LCDU/PC - LCDU/PC	2	A to B	0.02 kg	1 pc.
47330200ZY	DCS patch cable LCDU/PC - LCDU/PC	3	A to B	0.03 kg	1 pc.
47330300ZY	DCS patch cable LCDU/PC - LCDU/PC	4	A to B	0.03 kg	1 pc.
47330400ZY	DCS patch cable LCDU/PC - LCDU/PC	5	A to B	0.04 kg	1 pc.
47330500ZY	DCS patch cable LCDU/PC - LCDU/PC	6	A to B	0.04 kg	1 pc.
47330600ZY	DCS patch cable LCDU/PC - LCDU/PC	7	A to B	0.04 kg	1 pc.
47330700ZY	DCS patch cable LCDU/PC - LCDU/PC	8	A to B	0.05 kg	1 pc.
47330800ZY	DCS patch cable LCDU/PC - LCDU/PC	9	A to B	0.05 kg	1 pc.
47330900ZY	DCS patch cable LCDU/PC - LCDU/PC	10	A to B	0.06 kg	1 pc.
47311100ZY	DCS patch cable LCDU/PC - LCDU/PC	11	A to B	0.47 kg	1 pc.
47311200ZY	DCS patch cable LCDU/PC - LCDU/PC	12	A to B	0.06 kg	1 pc.
47311300ZY	DCS patch cable LCDU/PC - LCDU/PC	13	A to B	0.07 kg	1 pc.
47311400ZY	DCS patch cable LCDU/PC - LCDU/PC	14	A to B	0.07 kg	1 pc.
47311500ZY	DCS patch cable LCDU/PC - LCDU/PC	15	A to B	0.08 kg	1 pc.

Intelli-Cross® is a registered trademark of SEIKOH GIKEN Co., Ltd.