

Phone panels CU 25/4

unshielded, loaded with 25 RJ45 jacks, Category 3



Phone panel CU 25/4

Description

Unshielded 19"/1U phone panels for the transmission of digital (ISDN) and analogue voice signals.

Especially suitable for all Class C applications in accordance with EN 50173-1 and ISO/IEC 11801.

The patch panels support cables up to 50 pairs (telephone cables).

A maximum of four wires may be connected to one RJ45 socket. A termination aid is available as an optional accessory. This consists of two angular sheets that can easily be fixed to the frame or cabinet and make the cable termination more comfortable. For more accessories see below.

General Properties

Design	straight
Loaded / Unloaded	Loaded - RJ45 Cat.3
Number of ports	25

Electrical properties

Category	3
EMC	unshielded

Mechanical properties

Connection type	LSA
Mounting method	482.6 mm (19 inch) mounting
Screened	No
Type of connector	RJ45 8(8)

Standards

Cat./Class	better than Cat.3
------------	-------------------

Versions

Material number	Product	Outer dimensions (HxWxD)	Colour	Weight [kg]	Packing unit
418000	Phone panel CU 25/4 with 25x RJ45 jacks, Cat.3	1 U, 44 mm x 482 mm x 129 mm	light grey	1.3 kg	1 pc.
418002	Phone panel CU 25/4 with 25x RJ45 jacks, Cat.3	1 U, 44 mm x 482 mm x 129 mm	black	1.35 kg	1 pc.